


MSDS - Cling PVC, Static Film



Page 1 of 2

Emergency Contact:

Grafix, Inc.
19499 Miles Rd.
Cleveland, Oh. 44128
(216) 581-9050

Product Identification:

Soft polyvinyl chloride sheet.

Hazardous Ingredients:

This material is not a "health hazard" as defined under the OSHA Hazard Communication Standard, 29 CFR 1910.1200 or S.A.R.A. Title III, Section 313. This material is considered an article under OSHA and TSCA standards. Under normal use conditions, release would be below OSHA limits.

Physical-Chemical Data:

The film is can be clear or various colors and is odorless. This film has a flash point at 400°C and decomposes at 400°C and may emit HCL. It has a vicat-softening range of 70°C.

Physical Hazards:

Film movement may develop electrical charges. This can provide a source for flammable vapours or give electrical shock. Use static eliminators if necessary. Keep away from heat and sources if ignition. No evidence of any irritant effects from normal handling and use.

Health Hazard Data:

No adverse health effect have been attributed to this clong film.

Hazard Designations

		Key
Health:	0	0-None
Flamability	2	1-Slight
Reactivity	0	2-Moderate
		3-Severe
		4-Extreme

GRAFIX® Plastics

A Division of GRAFIX, Inc.

19499 Miles Rd. Cleveland, OH. 44128


(800) 447-2349 (216) 581-9050 FAX (216) 581-9041

E-MAIL info@grafixplastics.com WEB <http://www.grafixplastics.com>



MSDS - Cling PVC, Static Film

Page 2 of 2



Control Measure and Safe Handling Procedures

The film will burn if exposed to flame. Burning is accompanied by melting and dripping which may cause the fire to spread. Combustion will evolve toxic and irritant vapors. Fire fighters should protect themselves from decomposition and combustion products that may include HCL, carbon monoxide and other such toxic gases. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exist. Fire fighting extinguishing media include carbon dioxide, water spray or dry chemical.

If the film could be subject to conditions releasing HCL, then adequate ventilation should be used to stay below the TLV, or self-contained breathing apparatus should be used.

Disposal and Shipping Information:

Cling PVC film is not classified as hazardous waste under the Resource Conservation and Recovery Act, and unless prohibited by state or local regulation, can be disposed of in a municipal landfill or incinerated. This product is not classified by the U.S. Department of Transportation as a hazardous material.

Information Contact:

Grafix, Inc.
19499 Miles Rd.
Cleveland, OH. 44128

To the best of our knowledge the information contained herein is accurate. However, Grafix assumes no liability whatsoever, for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All material may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the on hazards which exist.

GRAFIX® Plastics

A Division of GRAFIX, Inc.

19499 Miles Rd. Cleveland, OH. 44128

(800) 447-2349 (216) 581-9050 FAX (216) 581-9041

E-MAIL info@grafixplastics.com WEB <http://www.grafixplastics.com>

